Description

tino

A special product from the LITHOFIN-Range for ceramics, quarry tiles and porcelain (KF). Lithofin KF Mildew-Away is a ready-to-use special cleaner based on active chlorine compounds with a wide range of cleaning and disinfecting properties. <u>Technical Data:</u> Density: approx. 1,1 g/cm³ Appearance: liquid, clear, yellowish

Odour: pungent pH-Value: approx. 13 Flash Point: n.a. Solubility in Water: complete

Properties

Lithofin KF Mildew-Away removes black mould and mildew spots as well as discolouration caused by plants. The product works quickly and efficiently, and through its preventive properties prevents further growth for a long time.

Field of Use

For removing mould and mildew from cement and silicone grouting, from tiles and plastic parts in sanitary areas as well as for removing mould and algae from masonry, concrete, natural stone and other similar surfaces.

Directions for Use

First remove the child-proof cap and replace it with the sprayer. Turn the nozzle to "spray" and, from a distance of approx. 15 to 20cm spray the product on the afflicted surfaces. Allow the product to work for 10 to 20 minutes, in very stubborn cases repeat the application after approx. 10 minutes. Then completely remove from the surface with plenty of water and a hard sponge or brush. Close the bottle with the childproof cap and clean the sprayer with water. Please Note: causes light stains on textiles. Do not spray on plants, textiles, metals such as iron, copper, nickel, aluminium, etc. Immediately remove splashes with plenty of water. Do not use on polished marble and sensitive glazed tiles and enamel. We highly recommend trying the product in an inconspicuous area prior to use.

<u>Advice:</u> in case of extreme mould growth on elastic joints, we recommend removing the joint material, spraying the open joint with plenty of Lithofin KF Mildew-Away and then closing the joint with new material.

Coverage: up to 5m² per 500ml.

Lithofin KF Mildew-Away

Storage

After use, remove sprayer and rinse well with water. Close bottle with child-proof cap. Keep in cool and dark conditions. Store bottle standing up. Use product within 6 months.

Environmental Protection

Surfactants are biologically degradeable in accordance with EU-regulations. <u>Disposal:</u> diluted product may be added to waste water. Containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection systems.

Safety

<u>Contents:</u> sodium-hypochlorite; non-ionic surfactants; auxilliary agents.

<u>Risk and Safety Phrases:</u> irritating to eyes Keep out of the reach of children. Do not breathe spray. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show this container or label. Do not mix with acids. Do not use in conjunction with other products, formation of dangerous gases possible. Use only in well-ventilated areas.

<u>First Aid Procedures:</u> remove contaminated soaked clothing immediately. In case of inhalation, ensure of fresh air. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

<u>Emergency Procedures:</u> in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). Ensure adequate ventilation. Product does not burn, fire-extinguishing activities according to surrounding. Special exposure hazards arising from the substance, combustible products or resulting gases: Chlorine (Cl2). Special protective equipment for fire fighters: Use breathing apparatus with independent air supply.

Additional Information is listed on the Material Safety Data Sheet.

ADR2003: not a dangerous good.

Packaging

500ml bottle with child-proof cap (10 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB11.04gps/12.02)