

### Lithofin MN Polish (liquid) for all natural and artificial stone

#### Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). Solvent based polishing liquid containing high quality waxes.

Note: Lithofin MN Polish (liquid) does not contain any environmentally problematic CHC's like trichlorethen or similar solvents.

#### Properties

High quality raw materials guarantee optimal protective and maintenance properties, easy polishing and high durability. The first application already produces a polishable film, which can be brought to a high gloss through polishing by hand or machine. Lithofin MN Polish (liquid) improves the stone's appearance by enhancing the colour structure and facilitates regular maintenance.

#### Technical Data:

Density: approx. 0,80 g/cm<sup>3</sup>

Appearance: liquid, colourless, clear

Odour: aromatic

pH-Value: n.a.

Appearance: liquid, clear, colourless

Aroma: Odourless

Flash Point: >23°C

Solubility in Water: not soluble

Durability: resistant to regular household dirt and salt, not resistant to petrol and similar substances. Depending on the level of wear and tear, the product's effect will last for several months.

#### Field of Use

For the initial treatment of newly installed natural and engineered stone surfaces, window sills, table tops, etc. to improve the appearance and provide protection.

Also to freshen up worn and dull stone surfaces.

Surfaces: all finely honed and polished natural stones such as marble, limestone, travertine, slate, granite, etc. as well as engineered stone, aggro marble and terrazzo.

#### Directions for Use

Shake bottle before use. Thinly and evenly apply Lithofin MN Polish (liquid) with a clean cloth and allow the product to dry. Then polish with a soft linen cloth or polishing pad. Highly absorbent surfaces may have to be treated more than once.

Please Note: the surface to be treated must be completely clean and dry. Do not apply in temperatures below 15°C and above 25°C. Protect surfaces sensitive to solvents. Lithofin MN Polish (liquid) is suitable for indoor use only. Well honed surfaces are a prerequisite for good results. In case the application is patchy, polish off with steel wool (000). Layer forming products affect the slip resistant properties of the surface. We highly recommend trying the product in an inconspicuous area prior to use. Lithofin MN Polish (liquid) can be removed with Lithofin MN Power-Clean or in extremely stubborn cases with Lithofin WAX-OFF.

On smaller surfaces, use Lithofin MN Polish Cream.

Coverage: 15 to 20m<sup>2</sup>/Ltr. depending on the surface.

Drying Time: after 5-10 min. ready for polish, completely dry after 50-60 min.

#### Storage

Keep closed and dry at room temperature. In low temperatures, the product may become cloudy. Place bottle in hot water and shake until clear again. Shelf life approx. three years.

#### Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate.

Clean containers can be recycled through collection systems.

#### Safety

Contents: waxes; acrylates; xylol; auxiliary agents.

Risk and Safety Phrases: flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not breathe vapour.

Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

First Aid Procedures: remove contaminated soaked clothing immediately. In case of inhalation, ensure of fresh air. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional Information is listed on the Material Safety Data Sheet.

ADR2003:

flammable liquid, n.o.s.

UN 1993, Class 3

Packaging Group III

#### Packaging

1 litre bottle with child-proof cap (10 per box)

5 litre canister (2 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB12.07/12.07)

#### Agents for Great Britain:

CASDRON Enterprises Ltd. • Alresford, Hampshire SO24 9QF • Phone: +44 (0)1962 732 26 • Fax +44 (0)1962 735 373

Manufactured in Germany by: LITHOFIN AG • 73240 Wendlingen • e-mail: info@lithofin.de

[www.lithofin.com](http://www.lithofin.com)