Lithofin Resin-EX Special Stripper Gel

Description
This special remover is based on acidic reaction compounds supported by select, highly active organic solvents. In many cases Lithofin Resin-EX can be used instead of (dangerous and environmentally harmful) CFC-based cleaning products.

Properties
Lithofin Resin-EX penetrates into many organic substances and dirt deposits, dissolving them from the surface. The gellike consistence simplifies the application.
Technical Data:
Density: approx. 1.1 g/cm³
Flash Point: >90°C(c.C.)
pH-Value: approx. 3
Appearance: whitish, dimish, gellike
Odour: slightly pungent
Solubility in Water: emulsifiable

Field of Use
To remove epoxy grout materials and residues. Also highly suitable for removing organic substances such as resins, sealants, coatings, oil and grease deposits, paint (graffiti), lacquer, adhesives, plastic residues, etc.
Suitable for indoor and outdoor use.
Surfaces: All quarry and ceramic tiles, rough natural stones such as granite, gneiss, quartzite as well as concrete and concrete stone.

Directions for Use
Test the product prior to use. Always apply to a dry surface. Protect surface from wetness during working time because water represses the effectiveness.
Application-/surface temperature: 10 - 30°C.
The mentioned working times are shorter at higher temperatures and longer at colder temperatures.

Directions to remove pavement fixing mortar
Generously apply to the dry surface using a brush or a scrubber. Allow to work for approx. 30 min. at room temp. of about 20°C. Then add water (best if diluted 1:10 with Lithofin MN Power-Clean) and brush. Afterwards, rinse and brush. Always brush diagonally to grouts. Rinse surface again with water.
In case of any leftovers, repeat when surface is dry.
Coverage: up to approx. 5 m²/L, depending on dirt.

Directions to remove epoxy resin (2K) mortar
Generously apply to the dry surface using a brush o a roller. Allow to work for approx. 2 hrs at about 20°C. Then use a rough pad (ex. green pad for glazed tiles) to work through. Add water and continue to scrub. Remove excess fluid and rinse with water immediately.
Coverage: up to approx. 20 m²/L on glazed tiles.

Storage
Cool and closed, shelf life of up to two years.

Environmental Protection
Free of chlorinated hydrocarbons (CHC). Contains organic solvents. WGK 1 after VwVwS from 17.5.99.
Disposal: AVV-Key 070604*. Dispose leftovers properly. Containers are made of environmentally friendly polyethylene (PE) and recyclable.
Clean containers can be recycled through collection systems (see product label).

Safety
As with all chemical products, avoid prolonged contact with skin or wear suitable protective gloves.
Ventilate application area.
Contents: <5% non-ionic surfactants; acids; auxilliary agents.
Labelling according to EU Regulations 1999/45/EG:
Symbol Xn, harmful.
Harmful by inhalation and if swallowed. Irritating to eyes and skin. Keep out of the reach of children.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed, seek medical advice immediately and show this container or label.
ADR2003: not a dangerous good

Packaging
a) 1 litre bottle with child-proof cap (10 per box)
b) 5 litre canister (2 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB1.09bs/8.08)

Agents for Great Britain:
CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 26 · Fax +44 (0)1962 735 373
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de **www.lithofin.com**