

## Lithofin MN Slate Oil

### Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). The ready-to use protective and care treatment contains high quality waxes and resins in CFC-free solvents.

#### Technical Data:

Density: approx. 0,80 g/cm<sup>3</sup>

Appearance: liquid, colourless, clear

Odour: aromatic

pH-Value: n.a.

Flash Point: >23°C

Solubility in Water: not soluble

### Properties

Lithofin MN Slate Oil invigorates the stones colours thereby accentuating the natural structure of the material.

Surfaces appear livelier and become water resistant.

Lithofin MN Slate Oil develops an elegant sheen which can be increased through polishing. The colour intensification of the product conceals stains which may be in the surface. Thick layers are not formed because a large portion of the old coat is removed when the product is reapplied.

Lithofin MN Slate Oil is therefore suitable for regular maintenance work.

### Field of Use

For initial treatment of newly installed surfaces such as floors, stairs, table tops, window sills, etc. Achieves a fresh look and protects the surface. Also suitable for touching up slate surfaces which have faded in colour. Highly suitable for regular care in order to maintain the colour-intensive appearance.

Surfaces: rough to finely honed clay slate surfaces, especially Indian, African and Italian slates.

For indoor use only.

### Directions for Use

Shake bottle before use.

Newly installed surfaces: the surface to be treated must be completely dry. Evenly and generously apply Lithofin MN Slate Oil with a sponge or cloth and allow it to dry.

Dirty and pre-treated surfaces: Apply generously and, after a few minutes, remove the dissolved residues with a cloth. Then apply again and allow to dry.

Please Note: always try the product in an inconspicuous area prior to use. The gloss level can be increased through polishing. If you are not satisfied with the result, apply again ensuring even distribution. In temperatures below 10°C, the product may flake. In this case, store the bottle in a warm place and shake until the product has turned clear again.

Drying Time: approx. 10 minutes.

Coverage: approx. 20m<sup>2</sup> per litre depending on the surface.

### Further Maintenance

Lithofin MN Slate Oil is suitable as a maintenance product due to its cleaning properties. In case of stubborn dirt deposits, use Lithofin MN Power-Clean. For regular maintenance, we recommend Lithofin MN Wash & Clean.

### Storage

Keep closed and dry. In temperatures between 10°C and 25°C. Shelf life of up to four years.

### Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate.

Clean containers can be recycled through collection systems.

### Safety

Contents: aliphatic and aromatic hydrocarbons; waxes; auxiliary agents.

Risk and Safety Phrases: flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not breathe vapour.

Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

First Aid Procedures: remove contaminated soaked clothing immediately. In case of inhalation, ensure of fresh air. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional Information is listed on the Material Safety Data Sheet.

#### ADR2003:

flammable liquid, n.o.s.

UN 1993, Class 3

Packaging Group III

### Packaging

1 litre bottle with child-proof cap (10 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB11.04gps/4.03)