

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weberfloor DPM hardener

Safety data sheet no.: 44P3177

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedford.

MK45 5BY

Tel: +44(0)1525 718877

Web: www.netweber.co.uk

email: sara.kelly@netweber.co.uk

1.4 Emergency telephone number: +44(0) 8703 330070 Office hours only (08.30-17.00 UK time)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361f Suspected of damaging fertility.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 1)

Hazard pictograms



GHS05 GHS07 GHS08

Signal word

 Danger

Hazard-determining components of labelling:

4-tert-butylphenol
m-phenylenebis(methylamine)
trimethylhexane-1,6-diamine

Hazard statements

H332 Harmful if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361f Suspected of damaging fertility.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.




vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 2119489419-21	4-tert-butylphenol  Repr. 2, H361f;  Eye Dam. 1, H318;  Skin Irrit. 2, H315	> 50%
---	---	-------

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 2)

CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 2119480150-50	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25 - 50%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 2119560598-25-xxxx	trimethylhexane-1,6-diamine ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2 - 5%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30 °C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Mount respiratory protective device.

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

PNECs	
25513-64-8 trimethylhexane-1,6-diamine	
Predicted No Effect Concentration	0.00295 mg/l (sea water rating factor)
	0.0295 mg/l (fresh water rating factor)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 4)

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls
Personal protective equipment:
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value:	Not applicable.
------------------	-----------------

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>200 °C (DIN)

Flash point:	108 °C (DIN ISO 2592)
---------------------	-----------------------

Flammability (solid, gaseous):	Not applicable.
---------------------------------------	-----------------

Ignition temperature:	350 °C (DIN 51794)
------------------------------	--------------------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Self-igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product does not present an explosion hazard.
-----------------------------	---

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 5)

Vapour pressure:	Not determined.
Density:	Not determined
Bulk density:	Not applicable.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent separation test:	Not determined
Solvent content:	
Organic solvents:	0.0 %
EU-VOC	0.00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
98-54-4 4-tert-butylphenol			
Oral	LD50	2951 mg/kg	(Rat)
Dermal	LD50	2288 mg/kg	(rbt)
Inhalative	LC50/4 h	> 5.6 mg/l	(Rat)
1477-55-0 m-phenylenebis(methylamine)			
Oral	LD50	930 mg/kg	(Rat)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 6)

Dermal	LD50	>3100 mg/kg (Rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
25513-64-8 trimethylhexane-1,6-diamine		
Oral	LD50	910 mg/kg (Rat)
Dermal	LD50	1280 mg/kg (Rabbit)

Primary irritant effect:
Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: Harmful to aquatic life with long lasting effects (H412).

Type of test		Effective concentration	Method	Assessment
98-54-4 4-tert-butylphenol				
LC50/96h	5.1 mg/l	(Oryzias latipes (Japanese medaka))		
EC50/48h	3.4 mg/l	(Daphnia magna)		
EC50/72h	22.7 mg/l	(Selenastrum capricornutum (Green algae))		
1477-55-0 m-phenylenebis(methylamine)				
LC50/96h	87.6 mg/l	(Oryzias latipes (Japanese medaka))		
EC50/48h	15.2 mg/l	(Daphnia magna)		
EC50/72h	20.3 mg/l	(Scenedesmus subspicatus (Algae))		
25513-64-8 trimethylhexane-1,6-diamine				
LC50/48h	174 mg/l	(Leuciscus idus (Orfe))		
EC50/24h	31.5 mg/l	(Daphnia magna)		
EC50/72h	29.5 mg/l	(Algae)		

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

Behaviour in environmental systems:
12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 7)

Ecotoxical effects:
Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Harmful to fish

Additional ecological information:
General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

Uncleaned packaging:
Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN2735

14.2 UN proper shipping name
ADR

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (4-tert-butylphenol, m-phenylenebis(methylamine))

IMDG, IATA

AMINES, LIQUID, CORROSIVE, N.O.S. (4-tert-butylphenol, m-phenylenebis(methylamine))

14.3 Transport hazard class(es)

ADR



Class

8 (C7) Corrosive substances.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31





Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 8)

Label	8+6.1
IMDG	
	
Class	8 Corrosive substances.
Label	8/6.1
IATA	
	
Class	8 Corrosive substances.
Label	8 (6.1)
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Corrosive substances.
EMS Number:	F-A,S-B
Segregation groups	Alkalis
Stowage Category	A
Segregation Code	SG35 Stow "separated from" acids.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (4 - T E R T - B U T Y L P H E N O L , M - P H E N Y L E N E B I S (M E T H Y L A M I N E)) , 8 (6 . 1) , II

GB

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.09.2016

Version number 1

Revision: 30.09.2016

Trade name weberfloor DPM hardener

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H361f Suspected of damaging fertility.
H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Quality Department

Contact: Dr S. Kelly; tel. + 44 (0) 1525 718877

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3