

PRODUCT TECHNICAL CHARACTERISTICS

PRODUCT TYPE	<i>Ceramic tile dry pressed $0.5\% < E \leq 3$</i>
GROUP	<i>B1b</i>
USE	<i>Wall</i>
MODEL	<i>NOLITA</i>
SIZE	<i>6,5X20</i>
COLOR	<i>ALL</i>

CRITERIA	NORME STANDARD	MINIMUM REQUIREMENTS	Bestile	
Dimension and superficial aspect	ISO 10545-2	Longitude	65	± 2mm
		Width	200	± 2mm
		Thickness	9,1	± 2mm
Groups of absorption of water	ISO 10545-3	$0.5\% \leq E \leq 3\%$ IND.MAX.3,3%	1,6	
Breaking charge N Thickness ≥ 7.5 mm	ISO 10545-4	1100	PERFORM	
Flexion resistance N/mm ²	ISO 10545-4	30	PERFORM	
Abrasion resistance PEI Clase	ISO 10545-7		I <input type="checkbox"/>	II <input type="checkbox"/>
			III <input checked="" type="checkbox"/>	IV <input type="checkbox"/>
Resistance of Craking	ISO 10545-11		Perform	
Frost Resistance	ISO 10545-12		Perform	
Thermal shock	ISO 10545-12		Perform	
Glide	CEN/TS 16165 (pendulum)		NPD	
	DIN 51130 (bare foot)		NPD	
Resistance to stains	ISO 10545-14	3	5	
Resistance to Household chemicals and: a) Acids b) Alkalis c) Swimming Pool Salts	ISO 10545-13	GLB GHB GB	GLA GHA GA	

Date	Responsable
26/2/19	Chief Laboratory